



1 PERFORMANCE DATA


**DIRECT FROSTED LOUVER
WITH ASSYMETRIC LENS
(DD1)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	111
	1000	9	115
	800	7	119
	700	6	122
	600	5	123
	500	4	124
	400	3	125
	300	3	125
	200	2	132


**DIRECT FROSTED LOUVER
WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	101
	1000	9	107
	800	7	109
	700	6	111
	600	5	115
	500	4	115
	400	3	115
	300	3	116
	200	2	121


**DIRECT BLACK LOUVER
WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	500	13	40
	400	9	42
	300	7	43
	200	5	45
	100	2	47


**DIRECT SATIN CHROME
LOUVER WITH COMFORT
LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	60
	700	11	60
	600	9	63
	500	7	65
	400	5	68
	300	3	68
	200	3	68
	100	2	69


**DIRECT SATIN GOLD
LOUVER WITH COMFORT
LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	59
	700	11	59
	600	9	62
	500	7	63
	400	5	66
	300	3	66
	200	3	66
	100	2	68


**DIRECT SATIN CHAMPAGNE
LOUVER COMFORT LENS
(DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	60
	700	11	60
	600	9	63
	500	7	65
	400	5	68
	300	3	68
	200	3	68
	100	2	69

INDIRECT BATWING (UD1)

	LUMEN/FT	WATT/FT	LPW
	1600	13	129
	1200	9	137
	1000	7	140
	750	5	146
	500	3	147
	250	2	152

**INDIRECT ASYMMETRIC
(UD3)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	750	8	103
	500	5	107
	250	2	112