



1 PERFORMANCE DATA

**DIRECT FROSTED LOUVER
WITH COMFORT LENS (DD4)**




LUMEN/FT	WATT/FT	LPW
1200	13	101
1000	9	107
800	7	109
700	6	111
600	5	115
500	4	115
400	3	115
300	3	116
200	2	121

**DIRECT BLACK LOUVER
WITH COMFORT LENS (DD4)**




LUMEN/FT	WATT/FT	LPW
500	13	40
400	9	42
300	7	43
200	5	45
100	2	47

**DIRECT SATIN CHROME
LOUVER WITH COMFORT
LENS (DD4)**




LUMEN/FT	WATT/FT	LPW
800	13	60
700	11	60
600	9	63
500	7	65
400	5	68
300	3	68
200	3	68
100	2	69

**DIRECT SATIN GOLD
LOUVER WITH COMFORT
LENS (DD4)**




LUMEN/FT	WATT/FT	LPW
800	13	59
700	11	59
600	9	62
500	7	63
400	5	66
300	3	66
200	3	66
100	2	68

**DIRECT SATIN CHAMPAGNE
LOUVER WITH COMFORT
LENS (DD4)**




LUMEN/FT	WATT/FT	LPW
800	13	60
700	11	60
600	9	63
500	7	65
400	5	68
300	3	68
200	3	68
100	2	69

INDIRECT BATWING (UD1)



LUMEN/FT	WATT/FT	LPW
1600	13	129
1200	9	137
1000	7	140
750	5	146
500	3	147
250	2	152

**INDIRECT ASYMMETRIC
(UD3)**



LUMEN/FT	WATT/FT	LPW
1200	13	97
1000	10	100
750	8	103
500	5	107
250	2	112