

1 PERFORMANCE DATA

DIRECT DIFFUSED (DD1 AND DS1)

	LUMEN/FT	WATT/FT	LPW
	1200	13	98
	1000	10	103
	800	8	106
	600	5	111
	400	3	115
	200	2	121

DIRECT DIFFUSED (DD3 AND DS3)

	LUMEN/FT	WATT/FT	LPW
	1400	13	122
	1200	11	126
	1000	9	131
	800	7	132
	600	5	136
	400	3	141
	200	2	143

DIRECT DIFFUSED (DD5 AND DS5)

	LUMEN/FT	WATT/FT	LPW
	1400	13	112
	1200	11	116
	1000	9	119
	800	7	122
	600	5	126
	400	3	130
	200	2	131

INDIRECT BATWING (UD1)

	LUMEN/FT	WATT/FT	LPW
	1650	13	132
	1400	10	137
	1200	9	140
	1000	7	144
	800	6	146
	600	4	150
	400	3	153
	200	1	153

INDIRECT OPAL DIFFUSER (UD2)

	LUMEN/FT	WATT/FT	LPW
	1650	13	128
	1400	10	132
	1200	9	135
	1000	7	139
	800	6	141
	600	4	144
	400	3	147
	200	1	150

INDIRECT ASYMMETRIC (UD3)

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	800	9	102
	600	6	107
	400	4	109
	200	2	112

EXTRA WIDE INDIRECT BATWING (UD4)

	LUMEN/FT	WATT/FT	LPW
	1400	13	113
	1200	10	116
	1000	9	119
	800	7	123
	600	5	127
	400	3	129
	200	2	131