





TRILOGY™


FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE




QUANTITIES

1 DESCRIPTION

2 OPTICS & FEATURES



Ceiling



Suspended
Direct/Indirect



Ceiling
Direct/Indirect

3 APPROVALS



IP20

4 GENERAL SPECIFICATION

BODY AND TRIM

Aluminium and steel.

FINISH

Gear tray, powder coated gloss white. Trim, powder coated.

SUSPENSION

Three cables.

LENS

Hand blown, triple ply, satin opal glass.

DRIVERS

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

DELIVERED LUMENS

Delivered lumens & LPW based on 4000K (min 80 CRI).

5 DESIGN OPTIONS

FINISH



¹ If the Halo Ring is not required, the top cover is White Gloss (FA56).

* If the Halo Ring is required, the top cover matches the Halo Ring color.

6 HOW TO ORDER

LUMINAIRE	CRI	CCT	HALO RING
TRLP Pendant (1270 lms) TRLC Ceiling (1270 lms)	CR80 CRI 80+ CR90 CRI 90+	CTA27 2700K CTA30 3000K CTA35 3500K CTA40 4000K	HRO Not required HR1 Halo Ring Required
FINISH FA01 White - Textured FA02 Black Metallic - Textured FA20 Silver Metallic - Textured FA25 Gold Metallic - Textured FA44 Midnight Blue Metallic - Textured FA45 Copper Metallic FA46 Charcoal Metallic - Textured FA47 Bronze Metallic - Textured FA52 Champagne Metallic FA53 Red Metallic - Textured FA56 White Gloss ¹ ¹ If the Halo Ring is not required, the top cover is White Gloss (FA56). [*] If the Halo Ring is required, the top cover matches the Halo Ring color.			

7 TECHNICAL DATA

LUMINAIRE

Code	TRLP	TRLC
Power (LED)	21W	21W
Delivered lms	1270	1270
LPW	61	61

8 DIMENSIONAL DIAGRAMS

