

AXALIS SQ™ - WALL SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



AXALIS SQ™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and extruded aluminum. Trim claws, die cast alloy.

Diffuser

Opal acrylic.

Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming (10%) standard.

Finish

Back plate, powder coated gloss white. Side trim, brushed aluminum. Trim claws, as listed.


Dust covers

Opal Polycarbonate.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall

AXALIS SQ™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

701050 701050

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. OPTIONS

TM Trim Claws, Silver Metallic

TB Trim Claws, Black Chrome

TC Trim Claws, Polished Chrome

TP Trim Claws, Polished Brass

TS Trim Claws, Satin Brass

TECHNICAL DATA

LUMINAIRE

Code	701050
Power (LED)	21W
Delivered lms	1676
LPW	81

APPROVALS



AXALIS SQ™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

