

BLADE III™ - WALL SURFACE EXTERIOR

Project Name:	Fixture Type:
Fixture Code:	Quantities:



BLADE III™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Body and trim

Die-cast aluminium.

Finish

Silver powder coated, RAL9006.

Front fascia

Injection molded plastic, UV stabilised, painted RAL9006. Front fascia can be custom painted to special order (Consult factory).

Gasketing

Heat resistant silicone.

Drivers

HPF, electronic for 120-277V (EU-240V).

Minimum Starting Temperature

-30°C.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Wall Up/Down

BLADE III™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

663004 663004 **663014** 663014 **663024** 663024 **663034** 663034

B. CCT

30 3000K (min 80 CRI) **40** 4000K (min 80 CRI) **B** Blue

C. DIMMING

DB Dimming 0-10V, 10%

TECHNICAL DATA

LUMINAIRE

Code	663004	663014	663024	663034
3 x 3W	Narrow Beam	Twin Beam	Medium Beam	Medium/Narrow Beam
Beam	10°	2x5°	40°	40°/10°
Delivered lms	3 x 236	3 x 236	3 x 236	3 x 236

APPROVALS



BLADE III™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

