





# BOX™


## FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

### 1 DESCRIPTION

**BOX** is a powerful downlight series with exceptional performance suitable for high ceiling applications. Equipped with high-efficiency reflectors optimized for beam definition and maximum center beam candela power, **BOX** delivers up to 12,900 lumens. Constructed of aluminum, the robust cuboid fits well with functionalist architecture. Available in single, double, and quad downlights that range from narrow, medium, and wide beam angles. With the options of Black, Silver Metallic, and White finishes, this fixture has a unique look for various spaces.

### 2 OPTICS & FEATURES



Ceiling



Declare

### 3 APPROVALS



4 GENERAL SPECIFICATION

**BODY AND TRIM**

Steel and aluminum.

**MECHANICAL**

Luminaires mount directly over J box (by others - North America only).

**DRIVERS**

HPF electronic, 120/277V (EU-240V) with 0-10V dimming (1%). The driver is integral to the fixture housing.

**REPORTED L70 @25°C (77°F)**

>55,000 hrs

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**SUSTAINABILITY**

Designed for on-site LED board, driver, and optic replacement.  
Contact the factory for maintenance documentation.

**FINISH**

Powder coated.

**MOUNTING**

Surface mount.

**SENSORS**

Consult factory regarding sensor compatibility.

**ESTIMATED L70 @25°C (77°F)**

>201,000 hrs

**APPROVALS**

Damp Rated.

5 HOW TO ORDER

| LUMINAIRE                                                                                                                                                                                      | CCT                                                                                          | REFLECTOR                                                                               | FINISH                                                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| <b>751001</b> 1, 3218 lms<br><b>751002</b> 2, 6436 lms<br><b>751004</b> 4, 12872 lms                                                                                                           | <b>30</b> 3000K (min 80 CRI)<br><b>35</b> 3500K (min 80 CRI)<br><b>40</b> 4000K (min 80 CRI) | <b>NB</b> Narrow Beam (14°)<br><b>MB</b> Medium Beam (22°)<br><b>WB</b> Wide Beam (38°) | <b>BL</b> Black<br><b>MS</b> Silver Metallic<br><b>WH</b> White |
| <b>DIMMING</b><br><b>D1</b> 0-10V Dimming (1%)<br><b>D2</b> 0-10V Dimming (0.1%)<br><b>DA</b> DALI Dimming (0.1%)<br><b>DL</b> DALI Dimming (1%)<br><b>L1</b> Lutron L3DA3W Hi-Lume 1%, 3 Wire |                                                                                              |                                                                                         |                                                                 |

6 TECHNICAL DATA

LUMINAIRE

| Code          | 751001 | 751002 | 751004 |
|---------------|--------|--------|--------|
| Power (LED)   | 37W    | 74W    | 148W   |
| Heads         | 1      | 2      | 4      |
| Delivered lms | 3218   | 6436   | 12872  |
| LPW           | 84     | 84     | 84     |

7 DIMENSIONAL DIAGRAMS

