

ERELLA™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



ERELLA™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Lens

Opal polycarbonate.

Luminaire orientation

Ceiling or wall mounted.

Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Trim, powder coated or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.


Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

OPTICS & FEATURES



ERELLA™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

600300 18", 1898 lms	600400 23", 2078 lms	600410 23", 2745 lms
-----------------------------	-----------------------------	-----------------------------

B. CCT

30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------	------------------------------

C. LENS

OP Opal Acrylic

D. FINISH

WH White	BM Bronze Metallic Textured	MS Silver Metallic	AB Antique Brass
PB Polished Brass	SB Satin Brass	PC Polished Chrome	SN Satin Nickel
F39 Other painted finish (RAL number required)	F40 Other Non-RAL painted finish (sample chip required)		

F39 & F40 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	600300	600400	600410
Power (LED)	28W	28W	36W
Delivered lms	1898	2078	2745
LPW	70	75	76
Diameter (A)	18"	23"	23"
Depth (D)	4"	4"	4"
Weight	8.1lb	9.9lb	9.9lb

APPROVALS



ERELLA™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

