

ERELLA™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



ERELLA™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Mechanical

Luminaires mount directly over a junction box (by others - North America only).

L70 @25°C (77°F)

> 50,000 hrs.

Suspension

Single tube with three support cables.

Lens

Acrylic.

Drivers


HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Remote Emergency


Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect

ERELLA™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

127010 23", 12714 lms	127020 29", 15439 lms	127030 33", 19334 lms	127040 46", 30973 lms
127050 56", 38150 lms			

B. CCT

30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------	------------------------------

C. FINISH

WH White	BM Bronze Metallic Textured	MS Silver Metallic	AB Antique Brass
PB Polished Brass	SB Satin Brass	PC Polished Chrome	SN Satin Nickel
F39 Other painted finish (RAL number required)	F40 Other Non-RAL painted finish (sample chip required)		

F39 & F40 have a one time set-up charge regardless of quantity.

D. LENS

OP Opal

E. DIMMING

DA DALI Drivers	DX DMX Drivers
------------------------	-----------------------

F. OPTIONS

RE Remote Emergency (max distance 10ft, 120/277V)	CB Cradle Bars	SW Swivel Canopy (42 Degrees)
--	-----------------------	--------------------------------------

G. SUSPENSION LENGTHS

S1 6" additional suspension length	S2 12" additional suspension length	S3 18" additional suspension length	S4 24" additional suspension length
---	--	--	--

ERELLA™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	127010	127020	127030	127040	127050
Power (LED)	128W	149W	170W	283W	350W
Delivered lms	12714	15439	19334	30973	38150
LPW	100	104	114	109	109
Diameter (A)	23"	29"	33"	46"	56"
Depth (D)	7"	9"	9"	12"	18"
Height (H)	17.5"	23"	23"	23"	29.5"

APPROVALS



ERELLA™ - SUSPENDED

DIMENSIONAL DIAGRAMS

