

MICRO SQ II™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO SQ II™ - WALL OR CEILING SURFACE

GENERAL SPECIFICATION

Body

Aluminium.

Lens

Frosted Polycarbonate.

L70 @25°C

> 50,000 hrs.

Finish

Powder coated.


Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers)40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

OPTICS & FEATURES



Ceiling Direct/Indirect Ceiling Direct Wall Direct/Indirect Wall Direct

MICRO SQ II™ - WALL OR CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

983405 983405	983410 983410	983420 983420	983430 983430
983440 983440	983505 983505	983510 983510	983520 983520
983530 983530	983540 983540		

B. CCT/COLOR (DIRECT)

D30 3000K (min 80 CRI)	D35 3500K (min 80 CRI)	D40 4000K (min 80 CRI)	DRD Red
DGN Green	DBL Blue		

C. CCT/COLOR (INDIRECT)

N30 3000K (min 80 CRI)	N35 3500K (min 80 CRI)	N40 4000K (min 80 CRI)	NRD Red
NGN Green	NBL Blue		

D. FINISH

BL Black	MS Silver Metallic	WH White	Z1 Wood Grain - Light Cherry
Z2 Wood Grain - Dark Walnut			

TECHNICAL DATA

LUMINAIRE

Code	983405	983410	983420	983430	983440	983505
Diameter (A)	24"	35"	48"	60"	73"	24"
Power (LED)	26W	39W	51W	70W	83W	31W
Light Distribution	Direct	Direct	Direct	Direct	Direct	Direct/Indirect
Delivered lms	3131	4689	6225	8574	10102	3767
LPW	120	120	122	122	122	122

Code	983510	983520	983530	983540
Diameter (A)	35"	48"	60"	73"
Power (LED)	47W	62W	84W	100W
Light Distribution	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect
Delivered lms	5628	7469	10292	12125
LPW	120	120	123	121

APPROVALS



MICRO SQ II™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

