





RAIL-LITE™


FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 DESCRIPTION

The multiple spot system blends into architecture and conceals the light sources for a discreet look. **RAIL-LITE** is ideal as a retail solution with ultimate beam control and high color rendering. The spots can be adjusted laterally within the channel to target more accurately and the angling of the beam adjusts in 5° increments up to 45°. A CRI of 90 displays the true color of objects making merchandise more distinguishable. With Twist'N'Lock vacuum-plated reflectors that aid in quick on-site switching, this luminaire is capable of narrow, medium, and wide beam illumination.


2 OPTICS & FEATURES



Recessed



Bridgelux-14°




Bridgelux-22°



Bridgelux-28°



Bridgelux-38°



Bridgelux-47°



Xicato-13°



Xicato-18°



Xicato-28°



Xicato-41°



Declare

3 APPROVALS



DAMP
LOCATION IP20

4 GENERAL SPECIFICATION

HOUSING

Steel and aluminum, black finish internal and external.

ROTATING

360° limit.

REFLECTORS

Narrow, medium and wide beam, highly reflective, specular finish, vacuum plated. Twist'N'Lock reflectors for on-site switching.

BEZEL TRIM VERSION

Extruded aluminum. For installation into ceilings with a thickness range of 1/2" to 3/4" (12mm-19mm).

POE

Rail-Lite can integrate into your data network via Power over Ethernet (PoE) connectivity.

LEDS

High power, LEDs can be replaced from below.

LINKS

<http://www.bridgelux.com/products/v-series#specifications>

<http://www.xicato.com/xtm-led-module/overview>

REPORTED L70 @25°C(77°F)

> 60,000 hrs.

NOTES

Photometric testing performed using LM79 procedures.
For all other reflectors types please consult photometric files.
Due to constant change in LEDs, please check our website for current product specifications.

Rail-Lite™ | Patent Pending (United States, Canada and European Patent Convention)

ANGLING

0° to 45° in 5° intervals.

LED HEAT SINK

Extruded aluminum.

DRIVERS

Constant Current driver for 120-277V (EU-240V). Drivers can be replaced from below. The driver is integral to the fixture housing.

SLIDING

Individual heads can slide a maximum of 2'/610mm left or right of its centre point.

ELECTRICAL

Integral junction box for branch circuit through wiring.

DELIVERED LUMENS

Delivered lumens & LPW based on 3000K (min 80 CRI).

SENSORS

Consult factory regarding sensor compatibility.

APPROVALS

Damp Rated.

SUSTAINABILITY


Designed for on-site LED board, driver, and optic replacement.
Contact the factory for maintenance documentation.

5 DESIGN OPTIONS

BEZEL FINISH



White



Black
Metallic
Textured



Silver
Metallic
Textured

6 HOW TO ORDER

LUMINAIRE 520112 300mm – 1 LED Head 520118 450mm – 1 or 2 LED Heads 520124 600mm – 2 or 3 LED Heads 520136 900mm – 2 to 4 LED Heads 520148 1200mm – 2 to 5 LED Heads 520160 1500mm – 2 to 5 LED Heads 520172 1800mm – 2 to 6 LED Heads 520196 2400mm – 2 to 7 LED Heads	NUMBER OF HEADS H01 1 LED Head H02 2 LED Heads H03 3 LED Heads H04 4 LED Heads H05 5 LED Heads H06 6 LED Heads H07 7 LED Heads	LEDs B27A Bridgelux V18, 2700K, 80 CRI, 3069 lms B27B Bridgelux V18, 2700K, 90 CRI, 2397 lms B30A Bridgelux V18, 2700K, 80 CRI, 3218 lms B30B Bridgelux V18, 3000K, 90 CRI, 2498 lms B35A Bridgelux V18, 3500K, 80 CRI, 3313 lms B40A Bridgelux V18, 4000K, 80 CRI, 3333 lms B40B Bridgelux V18, 4000K, 90 CRI, 2840 lms X27A Xicato Standard, 2700K, 83 CRI, 2262 lms X30A Xicato Standard, 3000K, 83 CRI, 2262 lms X35A Xicato Standard, 3500K, 83 CRI, 2262 lms X40A Xicato Standard, 4000K, 83 CRI, 2262 lms X30B Xicato Vibrant V80, 3000K, 83 CRI, 2262 lms X27C Xicato Artist, 2700K, 98 CRI, 2262 lms X30C Xicato Artist, 3000K, 98 CRI, 2262 lms X35C Xicato Artist, 3500K, 98 CRI, 2262 lms X40C Xicato Artist, 4000K, 98 CRI, 2262 lms X30D Xicato Vibrant V95, 3000K, 98 CRI, 2262 lms	
APERTURE 5W Narrow 6W Medium 9W Wide	BEZEL FINISH WH White BL Black Metallic Textured SL Silver Metallic Textured	BRIDGELUX REFLECTORS 529001 Narrow Beam 14° (125mm dia) 529002 Medium Beam 22° (125mm dia) 529003 Medium Beam 38° (75mm dia) 529004 Narrow Beam 28° (75mm dia) 529005 Wide Beam 47° (75mm dia)	XICATO REFLECTORS 529011 Narrow Beam 13° (125mm dia) 529012 Wide Beam 41° (125mm dia) 529013 Narrow Beam 18° (75mm dia) 529014 Medium Beam 28° (75mm dia)
DIMMING D1 0–10V Dimming (1%) D2 0–10V Dimming (0.1%) DA DALI Dimming (0.1%) DL DALI Dimming (1%) L1 Lutron L3DA3W Hi-Lume 1% 3 wire L2 Lutron LDE1 Hi-Lume 1% H EcoSystem DE PoE DE must be used with EV only.	OPTIONAL LOW VOLTAGE EV Low Voltage To be used with DE only.		

7 TECHNICAL DATA

LUMINAIRE

Code	520112	520118	520124	520136	520148	520160
Fixture Length	300mm - 1 LED Head	450mm - 1 or 2 LED Heads	600mm - 2 or 3 LED Heads	900mm - 2 to 4 LED Heads	1200mm - 2 to 5 LED Heads	1500mm - 2 to 5 LED Heads
Code	520172	520196				
Fixture Length	1800mm - 2 to 6 LED Heads	2400mm - 2 to 7 LED Heads				

LED TYPE


Code	B27A	B27B	B30A	B30B	B35A	B40A
Type	Bridgelux V18	Bridgelux V18	Bridgelux V18	Bridgelux V18	Bridgelux V18	Bridgelux V18
CCT	2700K	2700K	2700K	3000K	3500K	4000K
CRI	80	90	80	90	80	80
Power	38W	38W	38W	38W	38W	38W
Delivered lms	3069	2397	3218	2498	3313	3333
LPW	80	63	84	65	87	87
CBCP	29964	23408	31423	24391	32349	32541
Code	B40B	X27A	X30A	X35A	X40A	X30B
Type	Bridgelux V18	Xicato Standard	Xicato Standard	Xicato Standard	Xicato Standard	Xicato Vibrant V80
CCT	4000K	2700K	3000K	3500K	4000K	3000K
CRI	90	83	83	83	83	83
Power	38W	36W	36W	36W	36W	36W
Delivered lms	2840	2262	2262	2262	2262	2262
LPW	74	62	62	62	62	62
CBCP	27732	6201	6201	6201	6201	6201
Code	X27C	X30C	X35C	X40C	X30D	
Type	Xicato Artist	Xicato Artist	Xicato Artist	Xicato Artist	Xicato Vibrant V95	
CCT	2700K	3000K	3500K	4000K	3000K	
CRI	98	98	98	98	98	
Power	41W	41W	41W	41W	41W	
Delivered lms	2262	2262	2262	2262	2262	
LPW	55	55	55	55	55	
CBCP	6201	6201	6201	6201	6201	

APERTURE


Code	5W	6W	9W
Aperture	Narrow	Medium	Wide
A	125mm	162mm	229mm

8 DIMENSIONAL DIAGRAMS

Narrow Aperture



Medium Aperture



Wide Aperture

