

SURA OP™ - WALL SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



SURA OP™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and extruded aluminum.

Lens

Opal acrylic.

Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming standard (10%).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Side trim, powder coated gloss white.
Cover, finished as listed.


Dust covers

Opal Polycarbonate.

Mechanical

Luminaires mount directly to a junction box.

OPTICS & FEATURES



Wall Front/Back

SURA OP™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

411701 411701 **411713** 411713

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. COVER FINISH

WH White **MS** Silver Metallic **AB** Antique brass **SB** Satin brass
SN Satin nickel **OT** Other painted finish (RAL number required) **F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	411701	411713
Power (LED)	15W	21W
Delivered lms	1202	1714
LPW	82	82
Weight	4.4lb	4.4lb

APPROVALS



SURA OP™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

