





TRILOGY CRADLE™


FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 DESCRIPTION

2 OPTICS & FEATURES



Ceiling
Direct/Indirect

3 APPROVALS



DAMP
LOCATION



IP20

4 GENERAL SPECIFICATION

BODY AND TRIM

Steel and aluminum.

FINISH

Back plate, powder coated gloss white. Trim, painted or plated as listed.

LENS

Three ply satin opal glass.

DRIVERS

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

LUMINAIRE ORIENTATION

Ceiling or wall mounted.

DELIVERED LUMENS

Delivered lumens & LPW based on 3000K (min 80 CRI).

MECHANICAL

Mounts directly to a junction box (by others - North America only).

APPROVALS

Damp Location (Indoor use only).

5 HOW TO ORDER

LUMINAIRE	CCT	FINISH
638818 63 8818	30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)	WH White MB Metallic Bronze MS Silver Metallic PC Polished Chrome SC Satin Chrome SN Satin Nickel OT Other painted finish (RAL number required) F40 Other Non-RAL painted finish (sample chip required) OT & BL1 have a one time set-up charge regardless of quantity.

6 TECHNICAL DATA

LUMINAIRE

Code	638818
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	6.3Kg/14lb

7 DIMENSIONAL DIAGRAMS

