





WARP™


FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES


1 DESCRIPTION

Our dual circuit luminaire delivers high efficiency diffused, spot and direct light, allowing you to transition from general ambient to mood lighting. Available in two sizes 18" (457mm) & 24" (610mm), the **WARP** family offers two styles of pendant plus a ceiling mounted version. The color temperature of each light source can be individually selected to deliver an effect best suited to the application. New to the **WARP** are a wide array of contemporary decorative colors to accent your architectural scene.

2 OPTICS & FEATURES




Ceiling Direct



Direct



Spot Only 40°



Declare

3 APPROVALS



4 GENERAL SPECIFICATION

BODY

Aluminum and steel.

MECHANICAL

Luminaires mount directly to a J box (by others - North America only).

DRIVERS

HPF electronic drivers for 120-277V, 347V, (EU-240V). The driver is integral to the fixture housing.

LENS

Acrylic.

REMOTE EMERGENCY

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

SENSORS

Consult factory regarding sensor compatibility.

APPROVALS

Damp Rated.

DESIGNED BY

Serge Cornelissen.

REMOTE MOUNTING OF DRIVERS

Wire Size (max distance from canopy to drivers) 18 AWG - 9.5' (2.9m), 16 AWG - 19.5' (5.9m), 14 AWG - 29.5' (9.0m). Drivers must be accessible after installation.

INTEGRAL EMERGENCY SYSTEM

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency EU luminaires have a 10.5" (270mm) DIA x 2" (48mm) height canopy with LED charge indicator. Not available with a 347V supply.

DELIVERED LUMENS

Delivered lumens & LPW based on 4000K (min 80 CRI).

L70 @25°C

> 50,000 hrs.

DESIGN

US Pat. No. D893,083.

SUSTAINABILITY

Designed for on-site LED board, driver, and optic replacement. Contact the factory for maintenance documentation.

5 DESIGN OPTIONS

FINISH



6 HOW TO ORDER

LUMINAIRE WARC1P18 457mm, 3300 lms WARC1P24 610mm, 4900 lms	LUMENS LMA0200 2000 lm LMA0330 3300 lm LMA0490 4900 lm * Available for WARC1P24 only.	CRI CR80 CRI 80+	CCT CTA27 2700K CTA30 3000K CTA35 3500K CTA40 4000K
VOLTAGE V1 120/277V V2 240V ¹ V3 347V ² ¹ Not available in North America. ² Available with DA01 dimming only.	DIMMING DA01 0-10V Dimming 1.0% DA02 0-10V Dimming 0.1% ¹ DA20 DALI Dimming 0.1% ¹ DA21 DALI Dimming 1.0% ¹ DA30 DSI/switchDim ^{1 2} ¹ Not available with V3. ² Not available in North America.	FINISH FA01 White FA02 Black Metallic - Textured FA20 Silver Metallic - Textured FA25 Gold Metallic - Textured FA44 Midnight Blue Metallic - Textured FA45 Copper Metallic FA46 Charcoal Metallic - Textured FA47 Bronze Metallic - Textured FA52 Champagne Metallic FA53 Red Metallic - Textured	EMERGENCY E0 Not required E1 Emergency system - Integral E2 Emergency system - Remote
DIRECT SPOT DL00 Not required DL27 Downlight 28W, 2700K (1730 delivered lms) DL30 Downlight 28W, 3000K (1799 delivered lms) DL35 Downlight 28W, 3500K (1854 delivered lms) DL40 Downlight 28W, 4000K (1858 delivered lms) Beam angle for Downlight Spot is 40°.	CIRCUITS CS1 Single Circuit CS2 Dual Circuit		

7 TECHNICAL DATA

LUMINAIRE

Code	WARC1P18	WARC1P24
Diameter (A)	457mm	610mm
Wattage	22W	34W
Delivered lms	3300	4900
LPW	146	145
Height (B)	152mm	165mm

8 DIMENSIONAL DIAGRAMS

