

# WINDSOR™ - SUSPENDED

|               |               |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities:   |



# WINDSOR™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and brass.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Mechanical

Luminaires mount directly over a junction box (by others- North America only).

### L70 @25°C (77°F)

>50,000 hrs.

### Suspension

Single tube combined with three diagonal decorative tubes for stabilization.

### Lens

Acrylic.

### Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

### Remote Emergency


Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).


### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect

# WINDSOR™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

|                              |                              |                              |                              |
|------------------------------|------------------------------|------------------------------|------------------------------|
| <b>607010</b> 24", 12714 lms | <b>607020</b> 30", 15439 lms | <b>607030</b> 35", 22743 lms | <b>607040</b> 46", 30973 lms |
|------------------------------|------------------------------|------------------------------|------------------------------|

### B. CCT

|                              |                              |                              |
|------------------------------|------------------------------|------------------------------|
| <b>30</b> 3000K (min 80 CRI) | <b>35</b> 3500K (min 80 CRI) | <b>40</b> 4000K (min 80 CRI) |
|------------------------------|------------------------------|------------------------------|

### C. FINISH

|                                                                |                           |                         |                                                       |
|----------------------------------------------------------------|---------------------------|-------------------------|-------------------------------------------------------|
| <b>BM</b> Bronze Metallic Textured                             | <b>MS</b> Silver Metallic | <b>AB</b> Antique Brass | <b>PB</b> Polished Brass                              |
| <b>SB</b> Satin Brass                                          | <b>SC</b> Satin Chrome    | <b>SN</b> Satin Nickel  | <b>F39</b> Other painted finish (RAL number required) |
| <b>F40</b> Other Non-RAL painted finish (sample chip required) |                           |                         |                                                       |

F39 & F40 have a one time set-up charge regardless of quantity.

### D. LENS

|                |
|----------------|
| <b>OP</b> Opal |
|----------------|

### E. DIMMING

|                        |                       |
|------------------------|-----------------------|
| <b>DA</b> DALI Drivers | <b>DX</b> DMX Drivers |
|------------------------|-----------------------|

### F. ADDITIONAL SUSPENSION LENGTHS

|                                           |                                            |                                            |                                            |
|-------------------------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|
| <b>S1</b> 6" additional suspension length | <b>S2</b> 12" additional suspension length | <b>S3</b> 18" additional suspension length | <b>S4</b> 24" additional suspension length |
|-------------------------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|

### G. OPTIONS

|                                                            |                               |
|------------------------------------------------------------|-------------------------------|
| <b>RE</b> Remote Emergency (max distance 10 ft., 120/277V) | <b>SW</b> Swivel Canopy (42 ) |
|------------------------------------------------------------|-------------------------------|

# WINDSOR™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

| Code          | 607010 | 607020 | 607030 | 607040 |
|---------------|--------|--------|--------|--------|
| Power         | 128W   | 150W   | 212W   | 283W   |
| Delivered lms | 12714  | 15439  | 22743  | 30973  |
| LPW           | 100    | 104    | 107    | 109    |
| Diameter (A)  | 24"    | 30"    | 35"    | 46"    |
| Diameter (B)  | 5.3"   | 5.3"   | 5.3"   | 8.0"   |
| Height (H)    | 20"    | 21"    | 21"    | 24"    |
| Height (A)    | 3.9"   | 3.9"   | 3.9"   | 2.0"   |
| Depth (D)     | 9"     | 9"     | 15"    | 18"    |
| Weight        | 29lbs  | 33lbs  | 46lbs  | 84lbs  |

## APPROVALS



# WINDSOR™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

