

# ZEDOS SR™ - SUSPENDED

|               |               |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities:   |



# ZEDOS SR™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Suspension

Single tube with four decorative tubes.

### Lens

Acrylic.


### Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

### L70 @25°C (77°F)

> 50,000 hrs.

## OPTICS & FEATURES



Suspended Direct/Indirect



Direct-indirect

# ZEDOS SR™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**687210** 29", 15439 lms                      **687220** 37", 22631 lms                      **687230** 47", 30043 lms

### B. CCT

**30** 3000K (min 80 CRI)                      **35** 3500K (min 80 CRI)                      **40** 4000K (min 80 CRI)

### C. FINISH

**WH** White                      **BM** Bronze Metallic Textured                      **MS** Silver Metallic                      **PC** Polished Chrome  
**SB** Satin Brass                      **SC** Satin Chrome                      **SN** Satin Nickel                      **OT** Other painted finish (RAL number required)  
**F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

### D. LENS

**OP** Opal

### E. DIMMING

**DA** DALI Drivers                      **DX** DMX Drivers

### F. OPTIONS

**RE** Remote Emergency (man distance 10 ft, 120/277V)                      **CB** Cradle Bars                      **SW** Swivel Canopy (42 degrees)

### G. SUSPENSION LENGTHS

**S1** 6" Additional Suspension Length                      **S2** 12" Additional Suspension Length                      **S3** 18" Additional Suspension Length                      **S4** 24" Additional Suspension Length

# ZEDOS SR™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

| Code          | 687210 | 687220 | 687230 |
|---------------|--------|--------|--------|
| Power (LED)   | 150W   | 211W   | 282W   |
| Delivered lms | 15439  | 22631  | 30043  |
| LPW           | 103    | 107    | 107    |
| Diameter (A)  | 29"    | 37"    | 47"    |
| Diameter (B)  | 5.7"   | 5.7"   | 7.9"   |
| Depth (D)     | 6.5"   | 7"     | 9"     |
| Height (H)    | 24"    | 24"    | 29.5"  |
| Height (A)    | 1"     | 1"     | 1.75"  |

## APPROVALS



# ZEDOS SR™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

